

## CMEX-18 PRO

USB-3.0 high speed camera

DC.18000-Pro

### HIGHLIGHTS

- High speed camera
- 18.0 Mpix CMOS color USB 3.0 camera
- 1/2.3" sensor, 4912 x 3684 pixels
- Low signal/noise ratio
- USB 3.0 interface (USB 2.0 compatible)
- Perfect color-reproduction



DC.18000-Pro

### TECHNICAL SPECIFICATIONS

<b>Sensor</b>	CMOS 1/2.3 inch
<b>Pixels</b>	4912 x 3684 pixels, 18.0 Mpix
<b>Scan mode</b>	Progressive, rolling shutter
<b>Pixel size</b>	1.25 µm x 1.25 µm
<b>Filter</b>	RGB
<b>Mount</b>	C-mount
<b>Max fps</b>	Up to 8 frames per second (4912 x 3684 pixels) Up to 20 frames per second (2546 x 1842 pixels) Up to 34 frames per second (1228 x 922 pixels)
<b>Exposure</b>	Automatic or manual
<b>White balance</b>	Automatic/manual
<b>Dynamic range</b>	65 db
<b>S/N max</b>	42 db
<b>Data interface</b>	USB 3.0 high speed
<b>Operation</b>	0 – 50°C, 30-80 % humidity
<b>Storage temperature</b>	-20 to 60°Celsius
<b>Power supply</b>	5V over PC USB port
<b>Housing</b>	Integrated CNC aluminum alloy
<b>Supplied with</b>	0.5x objective with C-mount, USB 3 cable, 30 and 30.5 mm adapters for stereomicroscopes, 76 x 24 mm calibration slide (1mm/100), CD ROM with ImageFocus Alpha software, carton box

<b>Software</b>	Supplied with ImageFocus Alpha capture and measuring software For Win XP (32bit), Vista/ 7/ 8/ 10 (32 and 64 bit configurations) PC requirements: Compatible with Intel Core 2, 2.8 GHZ or higher, 2GB, USB-3 high speed
<b>Product number</b>	DC.18000-Pro



CMEX-18 Pro package content